

Contractor Series

Gasoline and Diesel-Powered Hot-Water Pressure Washers

www.nilfisk-alto.us



For more than 20 years, the KEW C3 pump has been the leader in the cleaning industry. With four fully ceramic pistons, stainless-steel valves and a brass cylinder head, this pump takes an inlet temperature up to 185°F.

Nilfisk ALTO

Contractor Series Hot Facts



KEY FEATURES

- High-performance, triple-pass burner
- KEW's renowned C3 pump
- Choice of gasoline or diesel engine power
- Powerful, heavy-duty cleaning capability with up to 3200 psi and 4.8 GPM
- Steam-cleaning capability

PRODUCT

- Heavy-duty cage-style frame with durable, powder-coated finish
- Designed for easy lifting with forks or sling
- Heavy-duty "triple-pass" vertical coil and burner with flame sensor to prevent burner flooding
- Thermostat, temperature indicator, pressure gauge and controls on a single, accessible panel
- Choice of 13-HP Honda OHV gasoline engine or 16-HP Ruggenerini diesel engine
- KEW's renowned C3, direct-drive, half-speed, four-cylinder pump engineered for heavy-duty industrial cleaning applications
- Burner fuel and air systems are driven direct -- no belts, generators or blower motors
- High-quality engine and component mounts eliminate harmful vibration

EASY TO USE

- Quick coupler inlet and high pressure hose
- Convenient storage for lance, hose and detergent
- Electric start standard
- All controls and indicators on one panel
- Burner refueled by swapping full container for empty; no pouring necessary

SAFETY

- All systems operate on 12 or 24 volts
- Flow-actuated un-loader with integral overpressure safety valve relieves hose pressure while machine is in bypass
- Dual flow switches control burner operation and flame sensor monitors for abnormal combustion

CONTRACTOR SERIES

SPECIFICATIONS	Master	Diesel Heavy Duty
Part Number	6239301	6239201
Pump Pressure (PSI)	3200	2900
Max. Water Flow (GPM)	4.8	4.6
Max. Water Temp (Full Pressure)	176°F	212°F
Max. Water Temp (Reduced Pressure)	302°F	302°F
Inlet Suction Lift	16 ft.	16 ft.
Engine Fuel Consumption (GPH)	0.9	0.8
Burner Fuel Consumption (GPH) (D=122°F)	1.5	1.5
Burner Fuel Tank Capacity	5 Gallons	5 Gallons
Engine HP	13 Honda	16 Ruggenerini
RPM	1750	1750
Nozzle	Tornado 05	Tornado 05
Size (L x W x H)	46 x 36 x 34 in.	46 x 36 x 42 in.
Weight	484 lbs.	693 lbs.

DISTRIBUTED BY:

Nilfisk-ALTO Cleaning Systems, Inc.
2100 Highway 265 South • Springdale, AR 72764
Phone: 877.366.2586 • Fax: 800.405.9092
info@altocsi.com • www.nilfisk-alto.us

**Nilfisk
ALTO**