

Vehicle data

Chassinummer (FIN)	W1T 964025 10 497848 5	Ordernummer	1 0 569 80263
Chassinummer (VIN)		Produktionsnummer	1316495
Anpassad fordonstyp	2653 L DNA6x2 B 13	Produktionsfabrik	0600 Wörth
Anpassad fordonstyp		Leveransdatum	2020-dec-28
Påbygggnationstyp	2	Vehicle ownership title number	

Aggregat

	Aggregatnummer	Variant	Objektnummer
Motor	471926 C0 609105	X110679010	X069703743
Avgasefterbehandling	930800 60 067247		
Växellåda	715381 G2 450723	X210229729	X062565760
Fördelningsväxellåda			
Framaxel 1	739566K0839404	X311001619	X066502390
Framaxel 2			
Framaxel 3			
Framaxel 4			
Bakaxel 1	748282G2922317	X350021963	X068507464
Bakaxel 2	749163J0025299		9613901299
Bakaxel 3			
Bakaxel 4			
Påbygggnation	960820 10 497848		
Kraftuttag			
Retarder			
Styrinrättning			

Elvarianter

Elvariant		Beteckning
Ledningssats 1	XVK81 361580	FRAME TRUNK CIRCUIT
Ledningssats 2	XVK82 005050	CROSSMEMBER TRUNK CIRCUIT
Ledningssats 3	XVK83 033227	ENGINE TRUNK CIRCUIT
Ledningssats 4	XVK84 324223	DASHBOARD TRUNK CIRCUIT
Ledningssats 5	XVK85 010776	FRONT PART TRUNK CIRCUIT
Ledningssats 6	XVK86 084764	ROOF TRUNK CIRCUIT
Ledningssats 7	XVK87 000323	DRIVER'S DOOR TRUNK CIRCUIT
Ledningssats 8	XVK88 000402	PASSENGER'S DOOR TRUNK CIRCUIT
Ledningssats 9	XVK89 014494	REAR WALL TRUNK CIRCUIT

Ledningssats 10

## Tekniska data

Kontaktläge

Servicenummer

Hastighetsmätare A 0125423517

K-värde

Impulsvärde 13290

## Utrustning - Färger

### Lack

Användning	Kod	Beteckning
Lackering 3	9147	arktikweiß
Lackering 2	9147	arktikweiß
Lackering 1	9147	arktikweiß
Lackering 4	9147	arktikweiß

Invändig utrustning 260A

## Utrustning - Däck

Däck 1	W48K26280
Däck 3	F18KPA480
Däck 2	F18K27481

## Utrustning - Övrigt

Lampor	Släpvnagskoppling
Vindrutetorkare	Vajervinsch
Värme	Fälgar

## Special equipment codes

Extrautrustningskodnummer	Beteckning
A1E	Front axle 9.0 t
A1Y	Front axle, straight version
A2G	Rear axle, crown wheel 300, planetary, 13.4 t
A4K	Trail. axle 10 t, de-loadable, liftable,twin tyres
A5P	Axle ratio i = 3.714
AA30	BREMSE KONTINUIRLICH

AA5P	ACHSUEBERSETZUNG I = 3,714
AB13	SCHEIBENBREMSSEN MIT TEILSCHUTZ
AB27	BREMSZYLINDER 20/24 HFL3
AC7C	CO2 WERT ACHSE;01L0106 1A3101
AI6X	LUFTFEDERUNG, HINTERACHSE
AR51	HALTER "LANG" (LEITUNGSFUEHRUNG HL7)
AZ26	KUPPLUNGSFLANSCH D180KV
AZB2	SCHEIBENBREMSE FA.WABCO
B1B	Electronic braking system with ABS and ASR
B1F	Heating, electronic air-processing unit
B1H	Electr. compressed air supply and control, centre
B2A	Disc brakes on front and rear axle
B2D	Cover plate for brake discs
B2X	Parking brake, electronic
B4A	Condensation monitoring, for compressed air sys.
B4M	Air reservoir, steel
B4Z	Air reservoir, additional
B5A	Trailer brake, 2-line, brake connections, left
B5D	Trailer Stability Control Assist (TSA)
B5L	Trailer brake connection, rear, Duo-Matic+Standard
C0T	Frame overhang 1650 mm
C2I	Wheelbase 4200 mm
C5M	Pre-installation, for bodies without subframe
C5P	Bolted frame
C6C	Steering, single-circuit
C6J	Power steering pump, uncontrolled
C6L	Power-assisted steering, reinforced, from 9 t
C6Q	Stabiliser, front axle
C6U	Extra anti-roll bar, rear/trailing axle
C7F	Front underride guard (ECE), aluminium
C7J	Battery carrier, batteries side by side
C8B	Rear wing, 2550 mm vehicle width
C8H	Wing, 3-piece, with EC splash guard
C8I	Splash guard (EC), front
C9S	Deletion mounting parts, on frame
C9Y	Deletion, rear underride guard (ECE)
CLW	Steering oil cooling
D0A	Leather steering wheel
D0S	Compressed-air connection, in cab

---

D1C	Driver's suspension seat, comfort
D1N	Fold-up co-driver's seat
D2N	Driver's seat backrest, release mechanism
D2W	Armrests on both sides, co-driver's seat
D3B	Luxury bed, bottom
D3M	Mattress, PremiumComfort, bottom
D3Q	Seat cover, velour, driver's seat
D3T	Seat cover, velour, co-driver's seat, centre seat
D4Z	Sunblind, side, driver's and co-driver's side
D5E	LED ambient lighting
D5O	StyleLine
D5Z	Carpet, engine tunnel
D6G	Automatic climate control
D6I	Residual engine heat utilisation
D6N	Hot-water auxiliary heater, cab and engine
D6Z	Construction-site filter
D7A	Heat insulation, additional
D7G	Stowage compartment lid, driver and co-driver side
D7J	Drawers, under bed
D7K	Drawer, under dash support
D7R	Stowage flaps, above windscreen
D8M	Sliding/tilting sunroof, electric, glass version
D9A	Pre-installation luxury bed, top, wide
E0D	Battery sensor, Hella
E0F	Batteries from company Exide
E1C	Batteries 2 x 12 V/220 Ah, low-maintenance
E1N	Alternator 28 V/100 A
E2J	Automatic cutouts
E3B	Connection point 12V/15A, for auxiliary consumers
E3M	Socket, 24 V/15 A, behind seat
E3R	Power socket, 24 V/25 A, co-driver footwell
E3W	PSM, 2nd generation
E4B	Interface, fleet management system FMS
E4C	Additional functions, for body manufacturer
E4X	Starting-off aid, with no time limit
E5A	No. 1 switch, for non-MB body electrics
E5B	No. 2 switch, for non-MB body electrics
E5H	Switch for night-time driving light
E6A	Trailer socket, 24 V, 15-pin

---

E6Y	Reverse warning, comb. with hazard warning lights
E7F	Cable remote control for air suspension
E9G	Provision for fitting electrical devices
E9I	Pre-inst., switch, lift axle, semitr./trailer
F0F	Side module, N3 vehicle
F0T	Mercedes star, illuminated from behind
F1E	L-cab StreamSpace, 2.30 m, tunnel 170 mm
F1R	L-cab
F2E	Floor var. tunnel 170mm, for stowage compart. left
F2G	Cab width 2.30 m
F2N	Cab, 600 mm attachment height
F2W	StreamSpace
F3C	Cab mountings, comfort, air-sprung
F3W	Cab tilting mechanism, mechanical-hydraulic
F3Z	Hydraulic tilting mechanism oil, below -25 degrees
F4H	Cab rear wall, without window
F4X	Stowage compartment exterior flap, left
F4Y	Stowage compartment exterior flap, right
F5I	Cab side deflectors, without air deflectors
F5L	Sun visor, exterior, transparent
F5Y	A-pillar trim
F6C	Windscreen, tinted
F6F	Sidewall window
F6I	Front mirror, heated
F6R	Air horns, cab roof
F6T	MirrorCam
F7B	Bumper, with steel corners
F7D	Bumper centre section w. towing eyes, coupling jaw
F7T	Door extension
F7X	Cab entrance, left/right, rigid
F8B	2 remote control keys
F8E	Locking system, with central locking
F8F	Extended central locking
F8V	Light sensor
F8W	Rain sensor
G0A	Powertrain, 44 t to 68 t
G0R	Transmission support arms, optimised for removal
G0T	Predictive Powertrain Control
G0W	Drive program offroad

G2F	Transmission G 330-12/11.63-0.77
G5B	Double-disc clutch
G5G	Mercedes PowerShift 3
GE12	TACHOGEBER SMART TACHO, KITAS 4.0, DIN-BAJONETT
GEN2	NEIGUNG GETRIEBE 3,5ø
GHS1	SAE I
GHSC	ZWEISCHEIBEN-KUPPLUNG
GK04	KUPPLUNGSFLANSCH D 180 KREUZVERZAHNT
GL01	LIEFERANT AMT GETRIEBESTELLER WABCO
GO14	GETRIEBEOELSTAND FUEL PERFORMANCE PACK OPTIMIERT
GOKC	TEMPERATURGEREGELTES OELKUEHLERSCHUTZVENTIL FGL100
GS31	GETRIEBESCHALTUNG AUTOMATISIERT
GT00	TRAGARME GESCHRAUBT
GXC1	TYPSCILDBESCHRIFTUNG TM DAIMLER TRUCK AG
GZ5E	MOTORKLASSE 5
GZS9	TCM WABCO 19.01 AB 01.08.2019
I2G	Tyres tubeless, 315/80 R 22.5, fr./lead./trl. axle
I2H	Tyres, tubeless, size 315/80 R 22.5, rear axle
I2P	Tyres tubeless, 385/65 R 22.5, fr./lead./trl. axle
I4D	Wheel arrangement 6x2, trailing axle, twin tyres
I5F	26.0-tonner
I6A	Rigid chassis
I6I	Vehicle production plant Wörth
I6K	Heavy-duty model series, new generation from 18 t
I6M	Heavy-duty vehicles from 18 t, off-road
I6X	Air suspension, rear axle
J10	Dig. tachograph, 2nd gen., working speed control
J1S	Tachograph manufacturer VDO
J2K	Speaker, 2-way system
J2O	Comfort telephony, wireless charging
J2U	Navigation system
J3U	Requirement: FleetBoard Manager app
J3V	Truck Data Center 7
J3Z	Axle load measuring device
J6C	Multimedia Cockpit, interactive
J6Y	Remote Online
J6Z	Preinstallation Mercedes-Benz Truck App Portal
J8Y	Pre-installation for Truck Data Center 7
J9A	Pre-installation for CB radio, 12 V, DIN slot

---

J9P	Pre-installation and display for up to 4 cameras
JCRC	Frame thickness 8 mm
K0T	Main tank, left
K1E	Tank, 390 l, left, 650 x 565 x 1250 mm, aluminium
K3V	AdBlue tank, 60 l, left
K5S	Protective cap for AdBlue metering system
K5Y	Initial filling, additional 30 litres of fuel
K7D	Exhaust system, tailpipe to right and outwards
L0A	Illumination regulation, in acc. with UN-R 48.06
L1A	Bi-xenon headlamps
L1D	Automatic main/dipped beam and cornering light
L1I	Fog lamps, LED daytime running lamps
L1P	LED tail lights
L2H	Side marker lamps, flashing
L3Z	Headlamp cleaning system
L9A	Pre-installation for rotating beacons
L9C	Pre-installation for additional headlamps, roof
L9G	Pre-installation for flood lamp, cab rear wall
M0C	Bottom shell to prevent swirling-up of dust
M0U	Noise encapsulation, special package
M3E	Eng. OM471, inline 6, 12.8 l, 390kW (530hp), 2600 Nm
M5B	2. Engine generation OM471
M5C	Engine version Euro VI, D
M5V	High Performance Engine Brake
M6L	Air compressor, 2-cylinder
M7I	Insect screen in front of cooling system
M7T	Water pump, governed
M8B	Air intake behind cab, mounted
M8Y	Fuel pre-filter, chassis-mounted, additional
MB17	ABGASSTUTZEN GERADE
MB50	ENGINE BRAKE POWER INCREASED
MC75	COOLANT PUMP DRIVE CONTROLLED
MDE9	CO2 OM471LA.6-8 1M4G4301E100E0281
ME19	MOTORAUSFUEHRUNG EUROVI D
MJF0	SOFTWARESTAND M 15.11.00.05
MLK4	LEISTUNG 390KW 2600NM
MN16	LENKHELFPUMPE AUSFUEHRUNG 4
MN48	MITNEHMER MIT ZAHNNABE ANALOG DIN 5462A 8X32X36
MT45	LADELUFTFUEHRUNG KALT, MIT DROSSELKLAPPE

---

MW46	OELWANNE THERMOPLAST BAUSTELLENFAHRZEUG FRONTSUMPF
N6Z	Transmission oil cooling
N7M	Engine PTO, rear, c, hydraulic pump ISO 7653D
00A	Coolant service interval, long for non-SWR
01C	Fuel pre-filter, 3rd position
01N	Detachable parts for offline cab
01Q	Scope of SFTP model generation 5
01T	Interior colour greige/anthracite
01Z	Steering, indirect
02F	PTO, NMV or engine, rear
02N	Starter Melco 95P65
08K	Driving Package
08O	Sight Package
Q1Y	Front spring, 9.0 t, 4-leaf
Q3Z	Lowered frame, with residual bellow pressure ctrl.
Q9C	Pre-inst. retrofit trail. coup. 5th-wheel trailer
R0Z	Wheel-nut cap
R1Q	15-degree tapered rims, 9.00 x 22.5
R1T	15-degree tapered rims, 11.75 x 22.5, front axle
S1D	Stability Control Assist (ESP)
S1H	Lane Keeping Assist
S1L	Attention Assist
S1O	Traffic Sign Assist
S1W	Active Brake Assist 5
S5A	Speed limiter, 90 km/h (56 mph), ECE
S5Z	Cruise control
S8A	First aid kit
S8C	Hazard warning triangle
S8D	Warning lamp
S8E	Reflective safety jacket
S8H	Fire extinguisher, 6 kg
U0Q	Control code, HDEP Fuel Efficiency Package - FE1
U1W	AdBlue lines, water-heated
U2G	Exhaust box
U2I	Control code EBS, 4th generation
U2M	Control code, ASAM
U2T	Control code, exhaust box, rear outlet
U3D	Control code, CAN star points, classic
U3F	Control code, global AdBlue sensor (GMS DEF)



---

U3L	Control code, catalytic converter kit 5
U3N	Control code, ABB map material, EU
U3Q	Control code, throttle valve
V0S	Vehicle class N3
V0X	Ground clearance under front axle, minimum 250 mm
V0Y	Ground clearance under rear axle, minimum 250 mm
V1B	Arocs
V1W	Standard
V2J	Arocs model generation 5
V8A	Chassis number FIN
W40	Weight variant 28.0 t (9.0/13.0/10.0)
X1I	Instrument/labels/documentation, Swedish
X2A	Model identification, acc. to weight variant
X2E	Model plate, EU
X2T	Digital Service Booklet
X3W	Powertrain warranty as per T and Cs 3yrs/450,000km
Y1B	Control of colours, high-runner colours
Y1H	Allocation OPP top coat line 3
Y1X	Pull-out refrigerator, under bed
Y4R	Inflation aid, for steep-shoulder rims
Y4W	Tool kit, extended
Y4Y	Tyre inflating hose
Y4Z	Compressed-air gun, with hose
Z1H	EBS, Wabco
Z1S	Level control equipment, item 1
Z1X	EAPU equipment, item 1
Z3A	Switch module 1, type A
Z3C	Switch module 2, type A
Z3D	Switch module 2, type B
Z3F	Switch module 7
Z3H	Side marker lights, 1st pair
Z3J	Side marker lights, 3rd pair
Z3K	Side marker lights, 4th pair
Z3N	Switch module 8B
Z3S	Front underride guard location 700 mm
Z3Z	Export code
Z40	Tank cross-section, narrow
Z4Q	Tank cross-section, low
Z5E	OM 471

---

Z5G	Fan position, on crankshaft
Z5K	Fan ratio, 1:1.2
Z5P	Clutch supplier F&S
Z5V	Starter with M10, HDEP
Z5X	Left-hand drive
Z5Y	Vehicle, for right-side traffic
Z7J	Aluminium battery lines
Z7K	Paint, additional control code
Z8P	CTT vehicle, conversion on assembly line
Z8U	CTT vehicle
Z9A	Constructability request order, special control

---